

A4 Colour Photocopier

# MX-C304W

Advanced A4 colour MFP that supports the office workflow environment



- Print, Copy, Scan, Fax, File
- Paper capacity: Std 300 Max 2700 sheets
- Single sign-on brings easy access to public cloud storage services
- Wireless LAN as standard and 2-line wired LAN support
- Pages per minute: 30 B/W, 30 Colour
- 7-inch colour LCD touchscreen with Easy UI mode
- Standard Duplex Single Pass Feeder (DSPF)
- Advanced data protection and access control with SSL validation and whitelisting

# Specifications

## GENERAL

Engine speed Colour ppm (A4)	30
Engine speed B/W ppm (A4)	30
Paper size: Min. -Max.	A6 - A4
Paper weight (g/m <sup>2</sup> )	Min - Max 55 - 220
Paper capacity:Std (sheets)	300
Paper capacity: Max. (sheets)	2700
Warm Up Time (sec.)	47
Memory general min/max (GB)	5
Harddisk	STD
Harddisk capacity (GB)	500
Duplex	STD
Power requirements - rated local AC voltage (Hz)	220 - 240V, 50 / 60Hz
Power consumption (kW)	1.84
Dimensions (mm)	491 x 568 x 565
Weight (kg)	38

## DOCUMENT FEEDER

Original capacity (sheets)	100
----------------------------	-----

## DOCUMENT FILING

Document filing (Standard / Option)	Std
Document filing capacity- main and custom folders (pages)	20,000
Document filing capacity- quick file folder (pages)	10,000
Stored jobs	Copy, print, scan, fax transmission
Storage folders	Quick files folder, main folder, custom folder (1,000 folders)
Confidential storage	•

## FAX

Fax (Standard / Option)	STD
Compression method	MH / MR / MMR / JBIG
Communication protocol	Super G3
Transmission time (sec)	2
Modem Speed (bps)	33.600 - 2.400
Transmission resolution	STD 203.2 x 97.8, Ultra Fine 203.2 x 195.6, Super Fine 203.2 x 391, Ultra fine 406.4 x 391
Document Size (Min)	A6
Document Size (Max)	A4
Memory (MB)	1
Grey Scale levels	256
Dial Registration; rapid/speed dial	2000

## WIRELESS LAN

Wireless LAN (Standard / Option)	STD
Compliant regulation	IEEE802.11n / g / b
Access mode	Infrastructure mode, Software AP mode
Security	WEP, WPA / WPA2-mixed PSK, WPA / WPA2-mixed EAP, WPA2 PSK, WPA2 EAP

## COPIER

Original paper size (Max.)	A4
First copy out time Colour (sec.)	6.7
First copy out time B/W (sec.)	5.5
E-sort Std	•
Continuous copy (Max. copies)	9999
Resolution Scan B/W (dpi)	600 x 600, 600 x 400
Resolution Scan Colour (dpi)	600 x 600, 600 x 400
Resolution Print (dpi)	600 x 600, 9,600 (equivalent) x 600
Gradation (equivalent levels) - B/W	256
Gradation (equivalent levels) - Colour	256
Zoom range (%)	25 - 400
Preset copy ratios	10 (5R / 5E)

## SCANNER

Network Scanner (Standard / Option)	STD
Scan method Push scan and Pull scan	•
Resolution push scan (dpi)	100, 200, 300, 400, 600
Resolution pull scan (dpi)	75, 100, 150, 200, 300, 400, 600, 50 - 9600 via user setting
File formats	TIFF, PDF, PDF / A-1a, PDF / A-1b, encrypted PDF, XPS, compact PDF, JPEG, searchable PDF, OOXML (pptx, xlsx, docx) text (TXT [UTF-8]), rich text (RTF)
Scan destinations Desktop	•
Scan destination FTP, Email	•
Scan destination Network folder	•
Scan destination USB memory	•

## PRINTER

Resolution (dpi)	600 x 600, 9600 (equivalent) x 600
Network Printer (Standard / Option)	STD
Interface Std/Opt	STD: USB 2.0, 10Base-T / 100Base-TX / 1000Base-T
Supported OS Standard	Windows 8.1, 10, Windows Server 2012, 2012R2, 2016, 2019, Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15
Network protocols	TCP / IP
Printing protocols	LPR, Raw TCP (port 9100), POP3 (email printing) HTTP, IPP, FTP for downloading print files, IPP, SMB, WSD
PDL Std/Opt	STD: PCL 6, Genuine Adobe® PostScript®3
Available fonts	80 fonts for PCL, 139 fonts for Adobe PostScript 3

## FINISHING

Output Capacity Max.	150
----------------------	-----

## TONER YIELD

Black (pages at 5% coverage)	6000
Cyan (pages at 5% coverage)	6000
Magenta (pages at 5% coverage)	6000
Yellow (pages at 5% coverage)	6000